

BILGE WATER SEPARATORS

ULTRA-SEP C Series

ULTRA-SEP C Series Bilge Water Separators meet your need for a small unit with a lower capital cost. Ideal for engine rooms where your installation space and budget are tight. C Series provide the same Positive Physical Barrier and continuous less than 5ppm discharge as Compass Water Solutions larger ULTRA-SEP systems but in a more compact size.



Benefits:

- Superior separation of emulsions with SPIR-O-LATOR® Membrane Technology. The Positive Physical Barrier to oil reduces risk of accidental overboard discharge.
- Continuous discharge with less than 5ppm oil content.
- Small footprint allows easy retrofit installation.
- Manual controls are simple and easy to operate.
- All units are pre-wired and pre-piped to facilitate easy installation and operation.
- IMO MEPC.107(49) / EC-MED type approved by USCG and ABS
- Updated design with improved pre-filter, simplified hydraulic flow, easy to read gauges and updated controls.

Options

- 5PPM-Calibrated Monitor
- In-Line Heaters
- Duplex Filtration Pre-treatment Skids









BILGE WATER SEPARATORS

ULTRA-SEP C Series

Model No.	Throughput	Length	Width	Height	Weight Dry	Oily Water Inlet	Processed Water Discharge	Oil Discharge	Power
	m³/h(gpm)	mm (in)	mm (in)	mm (in)	kg (lbs)	mm (in)	mm (in)	mm (in)	kW
US-500-C	0.5 (2.2) **	925 (37)	950 (38)	1525 (60)	243 (536)	25 (1.0)	25 (1.0)	25 (1.0)	3
US-1000-C	1.0 (4.4) ***	1015 (40)	1070 (42)	1550 (61)	299 (658)	25 (1.0)	25 (1.0)	25 (1.0)	4

[** 1.7 GPM Overboard; ***3.5 GPM Overboard]

